



TOTAL

TOTAL QUARTZ 3000 SJ 20W50

Motor Oil

THE BASICS

PASSENGER CAR RANGE



INTERNATIONAL SPECIFICATIONS

✓ API SJ/CF

Gasoline and diesel engine oils

SAE 20W-50

MINERAL TECHNOLOGY

APPLICATION

TOTAL QUARTZ 3000 SJ, multi-grade oils, designed for gasoline and diesel passenger cars. This lubricant can be used in standard conditions.

These products meet the requirements of most of car manufacturers. Suitable for standard services.

CLIENTS BENEFITS

- **TOTAL QUARTZ 3000 SJ oils** ensure a good **engine cleanliness thanks** to detergent and dispersant properties **prolonging the lifespan of the engine**
- Formulations are designed **to resist to oxidation effects between oil changes**

CHARACTERISTICS*

Tests	Unité	Method	20W-50
Density at 15 °C	kg/m ³	ASTM D1298	882
Kinematic viscosity at 40 °C	mm ² /s	ASTM D445	168
Kinematic viscosity at 100 °C	mm ² /s	ASTM D445	18
Viscosity index	-	ASTM D2270	120
Pour point	°C	ASTM D97	-24
Flash point COC	°C	ASTM D92	235

*The characteristics given above are obtained a standard tolerance threshold during production and may not be considered specifications.

RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance manual should be checked: oil changes should be carried out in accordance with the manufacturer's recommendations.

The product should not be stored at temperatures over 60°C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the packaging should not be exposed to the elements. Otherwise, the barrels should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

HEALTH, SAFETY AND ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your local reseller and is available for consultation at www.quickfds.fr.

This product should not be used for any purposes other than the ones for which it is intended.

When disposing of the product after use, please protect the environment and comply with local regulations.

TOTAL LUBRIFIANTS – Immeuble Spazio
562, avenue du Parc de l'île
92029 Nanterre cedex
France

TOTAL QUARTZ 3000 SJ
20W50

Technical data sheet update : March 2012

